Acapulco / Port Said

Ex-proof Light LEDs

karl-dose.com/**Acapulco** karl-dose.com/**Port Said**





Acapulco LED



1



504LED red

Port Said 504LED blue




Port Said 504LED green


Technical Data

Name & No.	Diagram	Wattage	kg	Description
Acapulco LED 5062	0-	max. 2 W	1,80	• IP 56 • Ex-proof LED light,
Acapulco LED 5062/D	-0-		1,90	ATEX certified: PTB 14 ATEX 1007 • brass casing made of RG5 EN 1982, guard made of CuZn33PbA, clear cylindrical glass, shock and heat resistant acc. to DIN 49993 • cable gland: KLE ATEX M20 x 1.5 brass • 1 x High Power LED, Type: P4Z • 12V / 24V DC • ambient temperature: -40°C up to +60°C • temperature class: T6 (any position) • pressure-proof Ex de IIB T6 • application: hazardous areas group IIB T6 (e.g. fueling vehicle lamp)
Port Said LED 504	_0_	10W	3,50	Pi IP 56 red cast brass casing and guard, glass clear cable gland: M20x1,5, on request M25x1,5 incl. LED PTB 06 ATEX 1046 X. Ex protection class: Eex de IIC T6, pressure resistant. certified according to EN 60079-0-2009

\$\frac{1}{2} \\ \frac{1}{2} \\ \frac



95 0 EMPCE 370 40 e



Acapulco LED

Port Said LED

Spare Parts

No.	kg	Description
5061SG	0,48	guard protector with glass, glued

Polished products available for an extra charge.

Also available with coloured LEDs, supplement charge.