

Optimal lighting for inland shipping



SCORPIUS LED



SCORPIUS LED 250

Searchlight

- + 29W, 10.400lm, 230V AC
- + Range at 1lx: 700m
- + Illuminated area at 100m: approx. Ø 14m
- + Rotation: 360°
- + Beam angle: 8°
- + Protection class: IP56
- + Corrosion-resistant aluminum
- + Color: RAL 9016 (other colors on request)
- + Available as deck, cabin, pedestal and remote version

Specially developed for the requirements of inland shipping.

GL DNV certified.

CERBERUS LED



CERBERUS LED

Floodlight

- + 26W, 3.450lm, 230V AC
- + From wide to narrow beam 14°/28°/54°
- + Protection class: IP66
- + Light color: 4.000k
- + Corrosion-resistant aluminum
- + Color: RAL 9016 (other colors on request)

Specially developed for the requirements of inland shipping.

Particularly robust floodlight, due to safety glass and aluminum cast.

Headquarters in Hamburg

KARL DOSE GmbH

Försterweg 73-77

22525 Hamburg

Germany

Contact us:

Website: www.karl-dose.com

Phone: 0049 (0)40 547322-0

Fax: 0049 (0)40 547322-99

E-Mail: sales@karl-dose.de



Optimal lighting for inland shipping



HEKA LED



- HEKA LED 131**
Classic ceiling light
+ 8W, 800lm, 230V AC, 24V DC
+ Beam angle: 120°
+ No ballast necessary
+ Almost indestructible brass case/IP56

MINOR LED



- MINOR LED 569**
Classic ceiling light
+ 4W, 400lm, 230V AC, 24V DC
+ Beam angle: 120°
+ No ballast necessary
+ Almost indestructible brass case/IP56

TARANDUS LED



- TARANDUS LED 17**
Downlight
+ 17W, 1.500lm, 230V AC
+ Beam angle: 120°
+ Corrosion-resistant aluminum case/IP56
+ Space saving



- TARANDUS LED 11**
Downlight
+ 11W, 1.200lm, 24V AC
+ Beam angle: 120°
+ Corrosion-resistant aluminum case/IP56
+ Space saving

AURIGA LED



- AURIGA VLED 1000 Floodlight**
+ 65W, 6.500lm, 230V AC, 24V DC
+ Beam angle: 10°/28°/62°
+ Light color: 6.300k
+ Corrosion-resistant stainless steel housing/IP67
+ Robust floodlight



- AURIGA VLED 200 Floodlight**
+ 34W, 3.400lm, 230V AC, 24V DC
+ Beam angle: 10°/28°/62°
+ Light color: 6.300k
+ Corrosion-resistant stainless steel housing/IP67
+ Robust floodlight

TUCANA LED



- TUCANA LED 20 Floodlight**
+ 167W, 18.950lm, 230V AC, 24V DC
+ Beam angle: 45°x20°/120°x120°
+ Light color: 4000k
+ Corrosion-resistant stainless steel housing/IP67
+ Ceramic board & heat sink for excellent thermal management



- TUCANA LED 6 Floodlight**
+ 60W, 5.678lm, 230V AC, 24V DC
+ Beam angle: 45°x20°/120°x120°
+ Light color: 4000k
+ Corrosion-resistant stainless steel housing/IP67
+ Ceramic board & heat sink for excellent thermal management

other sizes and combinations are possible

Headquarters in Hamburg
KARL DOSE GmbH
Försterweg 73-77
22525 Hamburg
Germany

Contact us:
Website: www.karl-dose.com
Phone: +49 (0)40 547322-0
Fax: +49 (0)40 547322-99
E-Mail: sales@karl-dose.de

