



Fidschi CES

Technical Data

No.	Thread Ø	Thread-length mm	For Cabel Ø mm	Package Pieces	Description
CES M 12	M 12 x 1,5 mm	5	3 - 6	100	<ul style="list-style-type: none"> • cable gland, brass nickel plated • with excellent strain relief • with fully insulated neoprene seal • wide clamping range • O-ring on outer thread • EN 50626 • protection type: IP68 - 5 bar • flat locknuts see Tonga Locknuts
CES M 16	M 16 x 1,5 mm	5	5 - 9	100	
CES M 20	M 20 x 1,5 mm	6	9 - 13	100	
CES M 25	M 25 x 1,5 mm	7	11 - 16	50	
CES M 32	M 32 x 1,5 mm	8	14 - 21	25	
CES M 40	M 40 x 1,5 mm	8	19 - 27	10	
CES M 50	M 50 x 1,5 mm	9	24 - 35	5	
CES M 63	M 63 x 1,5 mm	10	32 - 42	5	
CES PG 7	PG 7	5	3 - 6,5	100	
CES PG 9	PG 9	6	4 - 8	100	
CES PG 11	PG 11	6	5 - 10	50	
CES PG 13,5	PG 13,5	6,5	6 - 12	50	
CES PG 16	PG 16	6,5	10 - 14	50	
CES PG 21	PG 21	7	13 - 18	50	
CES PG 29	PG 29	8	18 - 25	25	
CES PG 36	PG 36	9	24 - 32	10	
CES PG 42	PG 42	10	30 - 38	5	
CES PG 48	PG 48	10	34 - 44	5	