



Lofoten M 12



Lofoten CG PG 11

**Technical Data**

No. Standard Cable	Thread	For Cable Ø mm	Package/Pieces	Description
CG M 12	M 12 x 1,5 mm	2 - 6,5	100	<ul style="list-style-type: none"> <li>• cable gland DIN EN 50262</li> <li>• IP 68-5 bar-, watertight made of polyamide</li> <li>• -30°C to +100°C</li> <li>• colour: RAL 7035</li> <li>• standard cable version type CG</li> <li>• multiple sealing insert on request</li> <li>• other colours on request</li> </ul>
CG M 16	M 16 x 1,5 mm	4 - 10	100	
CG M 20	M 20 x 1,5 mm	7 - 14	100	
CG M 25	M 25 x 1,5 mm	9 - 16	50	
CG M 32	M 32 x 1,5 mm	10 - 21	25	
CG M 40	M 40 x 1,5 mm	16 - 28	10	
CG M 50	M 50 x 1,5 mm	21 - 34,5	5	
CG M 63	M 63 x 1,5 mm	32 - 44,5	5	
CG PG 7	PG 7	3 - 6,5	50	
CG PG 9	PG 9	4 - 8	50	
CG PG 11	PG 11	5 - 10	50	
CG PG 13	PG 13,5	6 - 12	50	
CG PG 16	PG 16	10 - 14	50	
CG PG 21	PG 21	13 - 18	25	
CG PG 29	PG 29	18 - 25	25	
CG PG 36	PG 36	22 - 34	10	
CG PG 42	PG 42	30 - 38	10	
CG PG 48	PG 48	32 - 44,5	10	