



Cable Gland with PG-Type Connection Thread



Tonga



type of fitting "W"
for unscreened cable



type of fitting "Z"
for screened cable

Technical Data

No. Outfit "Z"	No. Outfit "W"	Thread Outside mm	Thread Inside mm	Outfit	Sealing ring Inner Ø mm DIN 89349	Washer Inner Ø mm DIN 89347	Nominal Size of Earthing Insert DIN 89345	For Kabel Ø mm	Description
187/PG 9 -Z..	187/PG 9 -W..	PG 9	M 18 x 1,5	Z 6 / W 6	18-06*	18-09	18-06	6,5 - 7,5	<ul style="list-style-type: none"> • brass cable gland acc. to DIN 89280 • screw-in-type with PG-thread • flat locknuts see Tonga Locknuts • example for purchase order: 186 / PG 11 - Z 17 186 / PG 21 - Z 17
187/PG 11 -Z..	187/PG 11 -W..	PG 11		Z 8 / W 8	18-08	18-09	18-06	7,5 - 8,5	
187/PG 13,5 -Z..	187/PG 13,5 -W..	PG 13,5		Z 10 / W 10	18-10	18-11	18-07	8,5 - 10,5	
187/PG 16 -Z..	187/PG 16 -W..	PG 16			24-08				
186/PG 9 -Z..	186/PG 9 -W..	PG 9	M 24 x 1,5	Z 8 A / W 8 A	24-08	24-09	24-06	7,5 - 8,5	
186/PG 11 -Z..	186/PG 11 -W..	PG 11		Z 10 A / W 10 A	24-10	24-11	24-07	8,5 - 10,5	
186/PG 13,5 -Z..	186/PG 13,5 -W..	PG 13,5		Z 12 / W 12	24-12	24-13	24-08	10,5 - 12,5	
186/PG 16 -Z..	186/PG 16 -W..	PG 16		Z 14 / W 14	24-14	24-15	24-10	12,5 - 14,5	
186/PG 21 -Z..	186/PG 21 -W..	PG 21		Z 16 / W 16	24-16	24-17	24-13	14,5 - 16,5	
186/PG 29 -Z..	186/PG 29 -W..	PG 29		Z 17 / W 17	24-17	24-18	24-14	16,5 - 17,5	
185/PG 11 -Z..	185/PG 11 -W..	PG 11	M 30 x 2	Z 15 / W 15	30-15*	30-19	30-16	14,5 - 16,5	
185/PG 13,5 -Z..	185/PG 13,5 -W..	PG 13,5		Z 18 / W 18	30-18	30-19	30-16	16,5 - 18,5	
185/PG 16 -Z..	185/PG 16 -W..	PG 16		Z 20 / W 20	30-20	30-21	30-18	18,5 - 20,5	
185/PG 21 -Z..	185/PG 21 -W..	PG 21			30-16	30-17	36-20	14,5 - 16,5	
185/PG 29 -Z..	185/PG 29 -W..	PG 29							
185/PG 36 -Z..	185/PG 36 -W..	PG 36							
184/PG 16 -Z..	184/PG 16 -W..	PG 16	M 36 x 2	Z 18 A / W 18 A	36-18*	36-23	36-20	16,5 - 18,5	
184/PG 21 -Z..	184/PG 21 -W..	PG 21		Z 22 / W 22	36-22	36-23	36-22	20,5 - 22,5	
184/PG 29 -Z..	184/PG 29 -W..	PG 29		Z 24 / W 24	36-24	36-25	36-24	22,5 - 24,5	
184/PG 36 -Z..	184/PG 36 -W..	PG 36		Z 26 / W 26	36-26	36-27	45-27	24,5 - 26,5	
184/PG 42 -Z..	184/PG 42 -W..	PG 42							
183/PG 21 -Z..	183/PG 21 -W..	PG 21	M 45 x 2	Z 28 / W 28	45-28	45-29	45-30	26,5 - 28,5	
183/PG 29 -Z..	183/PG 29 -W..	PG 29		Z 30 / W 30	45-30	45-31	45-30	28,5 - 30,5	
183/PG 36 -Z..	183/PG 36 -W..	PG 36		Z 32 / W 32	45-32	45-33	56-35	30,5 - 32,5	
183/PG 42 -Z..	183/PG 42 -W..	PG 42							
183/PG 48 -Z..	183/PG 48 -W..	PG 48							
182/PG 36 -Z..	182/PG 36 -W..	PG 36	M 56 x 2	Z 35 / W 35	56-35	56-36	56-39	32,5 - 35,5	
182/PG 42 -Z..	182/PG 42 -W..	PG 42		Z 38 / W 38	56-38	56-39	56-36	35,5 - 38,5	
182/PG 48 -Z..	182/PG 48 -W..	PG 48		Z 41 / W 41	56-41	56-42	72-44	38,5 - 41,5	
181/PG 42 -Z..	181/PG 42 -W..	PG 42	M 72 x 2	Z 44 / W 44	72-44	72-45	72-48	41,5 - 44,5	
181/PG 48 -Z..	181/PG 48 -W..	PG 48		Z 48 / W 48	72-48	72-49	72-52	44,5 - 48,5	
				Z 52 / W 52	72-52	72-53	72-52	48,5 - 52,5	
				- / W 56	72-56	72-57	-	52,5 - 56,5	

* Sondergröße (ähnlich DIN 89280)

Alle Kabeleinführungen gegen Mehrpreis auch in verchromter oder vernickelter Ausführung lieferbar.