



type of fitting "W"  
for unshielded cable

type of fitting "Z"  
for shielded cable



**Technical Data**

No. Outfit "Z"	No. Outfit "W"	Thread Outside mm	Thread Inside mm	Outfit	For Cable Ø mm	Sealing Ring Inner Ø mm DIN 89349	Washer Inner Ø mm DIN 89347	Nominal Size of Earthing Insert DIN 89345	kg/piece	Description
-	188 S/M .. - W 7	M 16 x 1,5	M 16 x 1,5	W 7	6 - 7,5	16-07	16-08	-	0,045	<ul style="list-style-type: none"> <li>• brass cable gland similar to DIN 89280</li> <li>• screw-in-type</li> <li>• thread acc. to EN 50262</li> <li>• flat locknuts see Tonga Locknuts</li> </ul>
187 S/M .. - Z	187 S/M .. - W 8	M 20 x 1,5	M 18 x 1,5	Z 6 / W 6	6 - 7,5	18-06	18-09	18-06	0,062	
	Z 8 / W 8			7 - 8,5	18-08	18-09	18-06	0,062		
	Z 10 / W 10			8 - 10,5	18-10	18-11	18-07	0,062		
186 S/M .. - Z	186 S/M .. - W	M 16 x 1,5 M 20 x 1,5 M 25 x 1,5 M 32 x 1,5 M 40 x 1,5	M 24 x 1,5	Z 8A / W 8A	7 - 8,5	24-08	24-09	24-06	0,095	
				Z 10A / W 10A	8 - 10,5	24-10	24-11	24-07	0,095	
				Z 12 / W 12	10 - 12,5	24-12	24-13	24-08	0,095	
				Z 14 / W 14	12 - 14,5	24-14	24-15	24-10	0,095	
				Z 16 / W 16	14 - 16,5	24-16	24-17	24-13	0,095	
185 S/M .. - Z	185 S/M .. - W	M 25 x 1,5 M 32 x 1,5 M 40 x 1,5	M 30 x 2	Z 17 / W 17	16 - 17	24-17	24-18	24-14	0,095	
				Z 15 / W 15	14,5 - 16,5	30-15	30-19	30-16	0,163	
				Z 18 / W 18	16 - 18,5	30-18	30-19	30-16	0,163	
184 S/M .. - Z	184 S/M .. - W	M 32 x 1,5 M 40 x 1,5 M 50 x 1,5	M 36 x 2	Z 20 / W 20	18 - 20,5	30-20	30-21	30-18	0,163	
				Z 18A / W 18A	16,5 - 18,5	36-18	36-23	36-20	0,220	
				Z 22 / W 22	20 - 22,5	36-22	36-23	36-20	0,220	
183 S/M .. - Z	183 S/M .. - W	M 40 x 1,5 M 50 x 1,6	M 45 x 2	Z 24 / W 24	22 - 24,5	36-24	36-25	36-22	0,220	
				Z 26 / W 26	24 - 26,5	36-26	36-27	36-24	0,220	
				Z 28 / W 28	26 - 28,5	45-28	45-29	45-27	0,370	
182 S/M .. - Z	182 S/M .. - W	M 50 x 1,5 M 63 x 1,5	M 56 x 2	Z 30 / W 30	28 - 30,5	45-30	45-31	45-30	0,370	
				Z 32 / W 32	30 - 32,5	45-32	45-33	45-30	0,370	
				Z 35 / W 35	32 - 35,5	56-35	56-36	56-35	0,495	
181 S/M .. - Z	181 S/M .. - W	M 63 x 1,5	M 72 x 2	Z 38 / W 38	35 - 38,5	56-38	56-39	56-39	0,495	
				Z 41 / W 41	38 - 41,5	56-41	56-42	56-36	0,495	
				Z 44 / W 44	41 - 44,5	72-44	72-45	72-44	0,725	
-	-	-	-	Z 48 / W 48	44 - 48,5	72-48	72-49	72-48	0,725	
				Z 52 / W 52	48 - 52,5	72-52	72-53	72-52	0,725	
				W 56	52 - 56,5	72-56	72-57	-	0,725	

For an extra charge all cable glands are also available with chrome plated or nickel plated galvanic surface.