



Tonga Mu M

Tonga Mu PG

Technical Data

No.	Thread mm	Key-width Hexagonal mm	Thickness mm	Package Pieces	Description
Mu PG 7	PG 7	15	2,8	100	<ul style="list-style-type: none"> • flat locknut of brass, nickel plated, DIN 46320 • with PG-thread
Mu PG 9	PG 9	18	2,8	100	
Mu PG 11	PG 11	21	3	100	
Mu PG 13,5	PG 13,5	23	3	100	
Mu PG 16	PG 16	26	3	100	
Mu PG 21	PG 21	32	3,5	100	
Mu PG 29	PG 29	41	3	50	
Mu PG 36	PG 36	51	3,5	50	
Mu PG 42	PG 42	60	3	50	
Mu PG 48	PG 48	61	3,5	50	
Mu M12	M 12 x 1,5 mm	15	2,8	100	<ul style="list-style-type: none"> • flat locknut of brass, nickel plated, DIN 46319 • with metric thread
Mu M20	M 20 x 1,5 mm	24	3	100	
Mu M25	M 25 x 1,5 mm	30	3,5	100	
Mu M32	M 32 x 1,5 mm	36	4	100	
Mu M40	M 40 x 1,5 mm	46	5	50	
Mu M50	M 50 x 1,5 mm	60	5	50	
Mu M63	M 63 x 1,5 mm	70	6	50	

* Special size (similar to DIN 89280)