

Floodlights

TUCANA LED

Through the innovative use of ceramics as a cooling system the TUCANA family creates luminous intensities of up to 30,000 lm without sacrificing durability. The housing is made of stainless steel adding to the robustness of the floodlights.

- + Attractive design
- + Excellent heat management
- + Simple assembly
- + LED modules can be exchanged easily

Technical Data

Material and color	Stainless steel powdercoated in RAL 9016, other colors on request
IP protection class	IP 67
Environmental temperature	-25°C to +40°C
Luminous flux	up to 30,000 lm
CCT (color)	4,000 K
Beam angle	45°x20°; 120°x120°



TUCANA 2

Luminous flux	approx. 2,000 lm
Input voltage	12 V DC, 24V DC, 230 V AC at 50/60 Hz
Wattage	max. 18 W
Weight	approx. 1.5 kg
Dimensions	H136xW168xD104 (mm)



TUCANA 4

Luminous flux	approx. 4,000 lm
Input voltage	24V DC, 230 V AC at 50/60 Hz
Wattage	max. 35 W
Weight	approx. 2.3 kg
Dimensions	H197xW168xD109 (mm)

Ranges and luminous flux were measured or calculated under laboratory conditions. The actual values depend on environmental factors such as rain or fog.